



LockersLockersLockers



WEC works with our customers to develop the best product package for each customer’s needs. WEC has focused on exceptional customer service while providing the most affordable and lowest total cost of ownership possible. The goal for WEC is to take satisfied customers and turn them into brand loyal customers. We listen to our customers and respond to our customer's needs with competence and integrity as well as knowledge.

WEC has expanded its capabilities becoming a national manufacturing and distribution company of commercial and industrial products. Since 1987, WEC is dedicated to our customers offering value-added services resulting in unsurpassed distribution and operational excellence.

Our Total Quality Management and Customer Relationship Management systems are considered best in class ensuring customers receive the best experience possible when purchasing the commercial products we sell. We don't just sell a product: we are your resource every step of the way. We achieve this by listening to our customer's needs and responding with fast, personal service. We must keep deliveries quick and on time, and offer the best possible pricing. We feel our value curve has the best total customer value proposition for customers. By providing functionality and flexibility, WEC is the solution to all your problems.

Locker Gauge & Metric Conversion




Series	Top	Back	Side	Bottom	Door	Door Frame	Shelf
DURABLE	24	24	24	16	16	16	24
DURABLE PLUS	24	24	24	16	14	16	24
COMPETITIVE	16	18	16	16	14	16	16
ATHLETIC	16	18	16	16	14	16	16
ALL WELDED PLUS	16	18	16	16	14	16	16




Gauge	U.S Std. Gauge Nominal Thickness (inches)	Millimeters
10	.1345	3.41
11	.1196	3.03
12	.1046	2.65
13	.0897	2.27
14	.0747	1.89
15	.0673	1.70
16	.0598	1.51
17	.0538	1.36
18	.0478	1.21
19	.0418	1.06
20	.0359	0.91
21	.0329	0.83
22	.0299	0.75
23	.0269	0.68
24	.0239	0.60
25	.0209	0.53
26	.0179	0.45
27	.0164	0.41






Inch to Millimeter Conversion Chart Rounded to nearest mm.					
In.	mm.	in	mm.	In.	mm.
¼	6	13	330	50	1270
3/8	10	13 5/8	346	53	1346
½	13	14 2/5	366	54	1372
1	25	15	381	60	1524
1-1/4	32	16	406	62	1575
1-1/2	38	16 1/4	413	63	1600
2	51	18	457	64	1626
2 3/4	70	20	508	65	1651
3	76	21	533	66	1676
4	102	24	610	67	1702
4 1/2	114	30	762	68	1727
5	127	31	787	69	1753
6	152	36	914	70	1778
7	178	37	940	72	1829
7 1/2	191	40	1016	74	1880
8	203	41	1041	75	1905
9	229	42	1067	76	1930
9 1/2	241	45	1143	77	1956
12	305	48	1219	78	1981

Locker Door & Sides

Series	Tiers (openings per frame)	Standard Door Style (Basis of Design)	Optional Door Style	Standard Sides Style (Basis of Design)	Optional Sides Style
Durable	1,2,3,4,5,6 2,7,8 person 16 Person Wall Mount	Louvers	Rectangular Perforations Diamond Perforations Mini Louvers Solid	Solid	Diamond Perforations
Durable Plus	1,2,3	Solid	Rectangular Perforations Diamond Perforations Mini Louvers Louvers	Solid	Diamond Perforations
Competitive	1,2,3,4,5,6,8,9	Diamond Perforated	Solid Louvers Mini Louvers	Diamond Perforated	Solid
Athletic	Open Front No Door	Foot Locker: Mini Louvers Security Box: Solid	Foot Locker: Solid Front Security Box: Louvers	Diamond Perforated	Solid
All Welded Plus	1,2,3,4,5,6,8,9	Diamond Perforated	Solid Louvers Mini Louvers Rectangular Perforations	Diamond Perforated	Solid

VENTILATION				
Standard Louvers	Diamond Perforations	Rectangular Perforations	Mini Louvers	Expanded Metal
				

HANDLE AND LATCHING TYPES			
Recessed Handle Multi-Point Latch	Recessed Handle Single Point Latch	Door Pull	Cremone Handle
			

TIER OPENINGS							
1 Tier	2 Tier	3 Tier	4 Tier	5 Tier	6 Tier	8 Tier	9 Tier
							

Locker Hinges & Door Handles

Series	Tiers (openings per frame)	Standard Hinge	Optional Hinges	Standard Door Handle & Latching Type	Optional Door Handle & Latching Type
--------	----------------------------	----------------	-----------------	--------------------------------------	--------------------------------------

Durable	1,2,3 2 person	16 gauge continuous piano type riveted to both door and frame	0.074" thick, 2" high, double spun, full loop, tight pin, five knuckle butt hinges. Welded to frame and riveted to the door.	Recessed Handle, Multi-Point Latch	Recessed Handle Single Point Latch
	4,5,6 16 Person Wall Mount			Friction Catch Door Pull	If any Other options are required please advise
Durable Plus	1,2,3	16 gauge continuous piano type riveted to both door and frame	No additional Charge	Recessed Handle, Multi-Point Latch	Recessed Handle Single Point Latch
Competitive	1,2,3	16 gauge continuous piano type riveted to both door and frame	No additional Charge	Recessed Handle, Single Point Latch	Recessed Handle Multi-Point Latch
	4,5,6,8,9			Friction Catch Door Pull	If any Other options are required please advise
Athletic	Open Front No Door	16 gauge continuous piano type riveted to both door and frame for both Security Box and Foot Locker		Security Box: Friction Catch Door Pull	If any Other options are required please advise
All Welded Plus	1,2,3	16 gauge continuous piano type riveted to both door and frame	No additional Charge	Recessed Handle, Multi-Point Latch	Recessed Handle Single Point Latch
	4,5,6,8,9			Friction Catch Door Pull	If any Other options are required please advise